

## Surface Mount Glass Passivated Ultrafast Rectifier

### Major Ratings and Characteristics

$I_{F(AV)}$	1.0 A
$V_{RRM}$	1300 V
$I_{FSM}$	20 A
$t_{rr}$	75 ns
$E_{AS}$	15 mJ
$T_j \text{ max.}$	150 °C



*Patented\**

\* Glass-plastic encapsulation technique is covered by patent No. 3,996,602, brazed-lead assembly by Patent No. 3,930,306 and lead forming by Patent No. 5,151,846

**DO-214BA (GF1)**

### Features

- Cavity-free glass-passivated junction
- Ideal for automated placement
- Ultrafast reverse recovery time
- Low switching losses, high efficiency
- Avalanche surge energy capability
- Meets environmental standard MIL-S-19500
- Meets MSL level 1, per J-STD-020C
- Solder Dip 260 °C, 40 seconds



### Mechanical Data

**Case:** DO-214BA, molded plastic over glass body  
Epoxy meets UL-94V-0 Flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002B and JESD22-B102D

E3 suffix for commercial grade, HE3 suffix for high reliability grade (AEC Q101 qualified)

**Polarity:** Color band denotes cathode end

### Typical Applications

For use in high voltage rectification of photoflash application

### Maximum Ratings

$T_A = 25\text{ °C}$  unless otherwise specified

Parameter	Symbol	EGF1T	Unit
Device Marking Code		ET	
Maximum repetitive peak reverse voltage	$V_{RRM}$	1300	V
Maximum RMS voltage	$V_{RMS}$	910	V
Maximum DC blocking	$V_{DC}$	1300	V
Maximum average forward rectified current	$I_{F(AV)}$	1.0	A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	$I_{FSM}$	20	A
Non-repetitive avalanche energy at $T_A = 25\text{ °C}$ , $I_{AS} = 1\text{ A}$ , $L = 30\text{ mH}$	$E_{AS}$	15	mJ
Operating junction and storage temperature range	$T_J, T_{STG}$	- 55 to + 150	°C

## Electrical Characteristics

$T_A = 25\text{ }^\circ\text{C}$  unless otherwise specified

Parameter	Test condition	Symbol	EGF1T	Unit
Maximum instantaneous	at 1.0 A, $T_j = 25\text{ }^\circ\text{C}$	$V_F$	3.0	V
Maximum DC reverse current	at $V_{RM}^{(1)}$ $T_j = 25\text{ }^\circ\text{C}$ $T_j = 125\text{ }^\circ\text{C}$	$I_R$	5.0 50	$\mu\text{A}$
Typical reverse recovery time	at $I_F = 0.5\text{ A}$ , $I_R = 1.0\text{ A}$ , $I_{rr} = 0.25\text{ A}$	$t_{rr}$	75	ns
Typical junction capacitance	at 4.0 V, 1 MHz	$C_J$	8.0	pF

Notes:

(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle

## Thermal Characteristics

$T_A = 25\text{ }^\circ\text{C}$  unless otherwise specified

Parameter	Symbol	EGF1T	Unit
Typical thermal resistance <sup>(1)</sup>	$R_{\theta JA}$ $R_{\theta JL}$	50 20	$^\circ\text{C/W}$

Notes:

(1) Thermal resistance from junction to ambient and from junction to lead, P.C.B. mounted on 0.95 x 0.95" (24 x 24 mm) copper pad areas

## Ratings and Characteristics Curves

( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise specified)




Figure 1. Maximum Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 5. Typical Junction Capacitance Per Leg




Figure 4. Typical Reverse Leakage Characteristics





Figure 6. Typical Transient Thermal Impedance

## Package outline dimensions in inches (millimeters)





### Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.